

# D1C-R300-13-840-015S



**recessed luminaire • round**

**Application :** General office area's, Auditoria, General education area's

**housing:** injection-moulded aluminium

**light source :** LED • 4000 K

**optics :** reflector • aluminium, specular with diamond facets • medium wide-angle

**UGR classification :** <=16

**luminous flux:** 1500 lm

**luminous efficacy :** 155 lm/W

**LLMF:** 96% @ 50khrs (Tq=25°C)

## Product information

### Mechanical properties

**dimensions :** 220 mm x 120 mm

**cut-out size :** 205 mm x 120 mm

**shape :** individual round

**colour:** RAL9003 - white

**trim:** wafer trim

**type :** individual luminaire

**IP:** IP20

### Electrical properties

**driver:** not dimmable

**power :** 9.7 W

**voltage :** 230-240V

**frequency :** 50Hz AC

**photobiological safety :** EN 62471: RISK GROUP 1  
UNLIMITED


## Luminance

luminous flux : 1500 lm

luminous efficacy : 155 lm/W

UGR classification =: <=16

luminous area : 0.02 m<sup>2</sup>



Average Luminances (Cd/m<sup>2</sup>) for 1500lm

Gamma	C0	C30	C45	C60	C90
45°	12408	12408	12408	12408	12408
50°	5416	5416	5416	5416	5416
55°	1633	1633	1633	1633	1633
60°	3	3	3	3	3
65°	0	0	0	0	0
70°	0	0	0	0	0
75°	0	0	0	0	0
80°	0	0	0	0	0
85°	0	0	0	0	0

## Classifications

CIE: 894 / 1000 / 1000 / 1000 / 1000

CIE FLUXCODE : 0.89 / 1.00 / 1.00 / 1.00 / 1.00

BZ: BZ1

CAE: Symmetrical

DIN: A60 (Nach Arbeitsblatt 7)

DIN\_U: Phi u = 1.00

DIN\_SU: Phi su = 0.81

UTE: 1.00 A + 0.00 T

This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.  
www.etaplighting.com // Made in Belgium

Lifetime Data (Tq=25.0°C)

Time(hrs)	LLMF(%)	Cx(%)
10000	99	2
20000	98	4
30000	97	6
40000	97	8
50000	96	9
60000	95	11
70000	95*	13
80000	94*	15
90000	93*	17
100000	93*	18

UGR classification =

Corrected Glare Ratings for a Total Lamp Flux of 1500lm (S = 0.25H)

	Room Reflection Factors (%)														
	Ceiling	Walls	Floor	70	70	50	50	30	70	70	50	50	30		
	70	70	50	50	30	70	70	50	50	30	70	70	50	50	30
	50	30	50	30	30	50	30	50	30	30	50	30	50	30	30
	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
Room Dimensions	Viewed Crosswise					Viewed Endwise									
X = 2H Y = 2H	17.0	18.3	17.2	18.6	18.8	17.0	18.3	17.2	18.6	18.8					
Y = 3H	16.8	18.0	17.1	18.3	18.6	16.8	18.0	17.1	18.3	18.6					
Y = 4H	16.7	17.9	17.1	18.1	18.4	16.7	17.9	17.1	18.1	18.4					
Y = 6H	16.6	17.7	17.0	18.0	18.3	16.6	17.7	17.0	18.0	18.3					
Y = 8H	16.6	17.6	17.0	17.9	18.2	16.6	17.6	17.0	17.9	18.2					
Y = 12H	16.6	17.5	16.9	17.8	18.2	16.6	17.5	16.9	17.8	18.2					
X = 4H Y = 2H	16.7	17.9	17.1	18.1	18.4	16.7	17.9	17.1	18.1	18.4					
Y = 3H	16.6	17.5	17.0	17.8	18.2	16.6	17.5	17.0	17.8	18.2					
Y = 4H	16.5	17.3	16.9	17.7	18.0	16.5	17.3	16.9	17.7	18.0					
Y = 6H	16.4	17.1	16.9	17.5	17.9	16.4	17.1	16.9	17.5	17.9					
Y = 8H	16.4	17.1	16.8	17.5	17.9	16.4	17.1	16.8	17.5	17.9					
Y = 12H	16.4	17.0	16.8	17.4	17.8	16.4	17.0	16.8	17.4	17.8					
X = 8H Y = 4H	16.4	17.1	16.8	17.5	17.9	16.4	17.1	16.8	17.5	17.9					
Y = 6H	16.3	16.9	16.8	17.3	17.8	16.3	16.9	16.8	17.3	17.8					
Y = 8H	16.3	16.8	16.7	17.2	17.7	16.3	16.8	16.7	17.2	17.7					
Y = 12H	16.2	16.7	16.7	17.1	17.7	16.2	16.7	16.7	17.1	17.7					
X = 12H Y = 4H	16.4	17.0	16.8	17.4	17.8	16.4	17.0	16.8	17.4	17.8					
Y = 6H	16.3	16.8	16.7	17.2	17.7	16.3	16.8	16.7	17.2	17.7					
Y = 8H	16.2	16.7	16.7	17.1	17.7	16.2	16.7	16.7	17.1	17.7					
UGR Variations with Observer Position for Luminaire Spacings S															
S = 1.0H	+3.4		-13.0		+3.4		-13.0								
S = 1.5H	+6.1		+0.0		+6.1		+0.0								
S = 2.0H	+8.1		+0.0		+8.1		+0.0								

Luminous intensities in cd

Gamma	Intensity for 1500lm		
	C0	C45	C90
0°	1236.6	1236.6	1236.6
5°	1253.1	1253.1	1253.1
10°	1209.6	1209.6	1209.6
15°	1142.7	1142.7	1142.7
20°	1149.5	1149.5	1149.5
25°	1048.1	1048.1	1048.1
30°	843.1	843.1	843.1
35°	631.2	631.2	631.2
40°	390.3	390.3	390.3
45°	206.2	206.2	206.2
50°	81.8	81.8	81.8
55°	22.0	22.0	22.0
60°	0.0	0.0	0.0
65°	0.0	0.0	0.0
70°	0.0	0.0	0.0
75°	0.0	0.0	0.0
80°	0.0	0.0	0.0
85°	0.0	0.0	0.0
90°	0.0	0.0	0.0

Colour properties

Correlated Colour Temperature : 4000

Ra: CRI (Ra) 80



## Efficiency

Utilisation Factors according to IES (%)

	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	30	30	30	0
Walls	50	30	10	50	30	10	50	30	10	0
Floor	20	20	20	20	20	20	20	20	20	0
RCR = 1	110	109	107	104	103	102	100	99	98	93
2	102	99	96	97	94	92	94	92	90	85
3	94	90	87	90	87	84	87	85	82	78
4	87	82	79	84	80	77	82	78	76	72
5	81	75	71	78	73	70	76	72	69	66
6	75	69	65	73	68	64	71	67	64	61
7	70	64	60	68	63	59	67	62	59	57
8	66	59	55	64	59	55	63	58	55	53
9	61	55	51	60	55	51	59	54	51	49
10	58	52	48	56	51	47	55	51	47	45

Utilisation Factors according to LiTG (%)

	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	50	50	30	0
Walls	50	30	50	30	50	30	50	30	30	0
Floor	30	30	10	10	30	30	10	10	10	0
k = 0.60	72	65	68	63	70	64	67	63	62	58
0.80	82	75	77	72	79	74	76	72	71	67
1.00	89	83	83	78	86	80	81	78	77	73
1.25	99	92	90	87	94	89	88	85	85	81
1.50	103	97	93	90	97	93	91	89	88	84
2.00	109	104	97	95	102	99	95	93	92	89
2.50	113	109	100	98	105	102	97	96	94	91
3.00	117	113	102	100	108	106	100	98	97	94
4.00	119	116	103	102	110	107	100	99	98	95
5.00	122	119	104	103	112	110	102	101	99	96

## Dimensional drawing

